

Are heterojunctions effective in a perovskite solar cell?

The construction of heterojunctions has been proven to be effective in optimizing the interface energy structure and passivating defect states in perovskite solar cells (PSCs). Tin (Sn)-based perov...

Can a heterojunction tune energy levels into perovskites?

This study considers the in situ introduction of a heterojunction capable of tuning energy levels into perovskites, where the energy level difference and the construction of a built-in electric field greatly improve the separation and migration efficiency of photogenerated carriers.

How are deterministic 2D/3D perovskite heterojunctions made?

In this study, the fabrication of deterministic 2D/3D perovskite heterojunctions is achieved using a solid-phase hot-pressing deposition method, wherein the investigation focuses on their growth mechanisms, energy level alignments, and film stabilities.

Can tin based perovskites form heterojunctions?

Tin (Sn)-based perovskites have been demonstrated to have good hole extraction capability and are promising candidates to form heterojunctions with Pb-based perovskites to facilitate the charge transfer. Here, we propose a strategy for the in situ construction of Pb/Sn-based perovskite heterojunctions by a solution method.

What is heterojunction formed by 3D-to-2D perovskite conversion?

Wen, J., Zhao, Y., Wu, P. et al. Heterojunction formed via 3D-to-2D perovskite conversion for photostable wide-bandgap perovskite solar cells.

What is Pb/Sn-based perovskite heterojunction?

Pb/Sn-Based Perovskite Heterojunction for Hole Transport Layer-Free Carbon-Based Perovskite Solar Cells  
The construction of heterojunctions has been proven to be effective in optimizing the interface energy structure and passivating defect states in perovskite solar cells (PSCs).

By integrating with the thermal-stable  $\text{FAPb}_{0.5}\text{Sn}_{0.5}\text{I}_3$  narrow-bandgap perovskites, our all-perovskite tandem solar cells exhibit a stabilized PCE of 28.1% and retain ...

Polycrystalline perovskite films feature distinct facet orientations on the surface, which give rise to diverse chemical and electronic landscapes. These facet variations manifest in differences in optoelectronic characteristics, including energy level alignment and carrier mobility. Heterojunction structures, a staple in traditional photovoltaic devices, involve the strategic ...

Scientists at Helmholtz Zentrum Berlin (HZB) announced on Monday 25.5% efficiency for a monolithic

perovskite-silicon heterojunction tandem cell and said reaching 32.5% is a realistic target.

Monolithic tandem Silicon-Perovskite cells are expected to even get up to 46% theoretical efficiency using a tailored top perovskite solar cell at  $E_g \sim 1.75$  eV [17b].

At the end of last year, perovskite solar cell developer Oxford Photovoltaics (PV) broke its own industry cell efficiency record after months of research on tandem silicon heterojunction ...

Modern photovoltaic devices are often based on a heterojunction structure where two components with different optoelectronic properties are interfaced. The properties of each side of the junction can be tuned by either utilizing different materials (e.g. donor/acceptor) or doping (e.g. PN Si junction) or even varying their dimensionality (e.g. 3D/2D). In this work ...

The new solar cell can be applied to almost any surface. Image: Oxford University. Scientists at the University of Oxford last week (9 August) revealed a breakthrough in solar PV technology via an ...

Fabricating perovskite heterojunctions is challenging. Now, Ji et al. form a phase heterojunction with two polymorphs of  $\text{CsPbI}_3$ , leading to 20.1% efficiency in inorganic perovskite solar cells.

Here we demonstrate the concept of phase heterojunction (PHJ) solar cells by utilizing two polymorphs of the same material. We demonstrate the approach by forming g ...

An international research team has developed a perovskite-silicon tandem solar cell that utilizes a bottom cell based on a heterojunction (HJT) design and improved hole transport layers (HTLs) ...

Session SI: Figure S1-S4, Quality check of the 2D perovskite layer on the 3D perovskite surface Figure S1. XRD patterns of directly deposited  $(\text{BA})_2(\text{MA})_{n-1}\text{PbI}_{3n+1}$  from the directly mixing precursor of BAI, MAI and  $\text{PbI}_2$  with the ratio of  $2:(n-1):n$ . To identify the  $2\theta = 9.1^\circ$ ; and  $13.7^\circ$  peaks

Web: <https://vielec-electricite.fr>